

2 & 3 Core & Earth Fire Rated

2 & 3 core & earth, copper conductors, 0.6/1kV X-HF-90 or X-HF-110 insulated, Orange HFS-90-TP or HFS-110-TP Sheathed to AS/NZS 5000.1 WS52W rated to AS/NZS 3013

Product Code	Nom. Cond. Area mm ²	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Earth Cond. Area mm ²	Nom. Overall Dia. mm	Approx. Mass kg/100m
--------------	---------------------------------	---------------------	---------------------------------	-----------------------------	----------------------------------	----------------------	----------------------

2 Core & Earth

2CE915BLVXZ	1.5	Cu	0.7	1.8	1.5	11.2	15
2CE925BLVXZ	2.5	Cu	0.7	1.8	2.5	12.5	20
2CE004BLVXZ	4	Cu	0.7	1.8	2.5	13.2	24
2CE006BLVXZ	6	Cu	0.7	1.8	2.5	14.1	28
2CE010BLVXZ	10	Cu	0.7	1.8	4	15.9	40
2CE016BLVXZ	16	Cu	0.7	1.8	6	17.8	55

3 Core & Earth

3CE915BLVXZ	1.5	Cu	0.7	1.8	1.5	12.2	18
3CE925BLVXZ	2.5	Cu	0.7	1.8	2.5	13.5	24
3CE004BLVXZ	4	Cu	0.7	1.8	2.5	14.4	30
3CE006BLVXZ	6	Cu	0.7	1.8	2.5	15.5	37
3CE010BLVXZ	10	Cu	0.7	1.8	4	17.6	53
3CE016BLVXZ	16	Cu	0.7	1.8	6	19.8	73