

## 4 Core & Earth Fire Rated

4 core & earth, copper conductors, 0.6/1kV X-HF-90 or X-HF-110 insulated, Orange HFS-90-TP or HFS-110-TP Sheathed to AS/NZS 5000.1 WS52W rated to AS/NZS 3013

| Product Code | Nom. Cond. Area mm <sup>2</sup> | Main Conductor Type | Nominal Insulation Thickness mm | Nominal Sheath Thickness mm | Earth Cond. Area mm <sup>2</sup> | Nom. Overall Dia. mm | Approx. Mass kg/100m |
|--------------|---------------------------------|---------------------|---------------------------------|-----------------------------|----------------------------------|----------------------|----------------------|
|--------------|---------------------------------|---------------------|---------------------------------|-----------------------------|----------------------------------|----------------------|----------------------|

### 4 Core & Earth

|             |     |    |     |     |     |      |     |
|-------------|-----|----|-----|-----|-----|------|-----|
| 4CE915BLVXZ | 1.5 | Cu | 0.7 | 1.8 | 1.5 | 13.2 | 21  |
| 4CE925BLVXZ | 2.5 | Cu | 0.7 | 1.8 | 2.5 | 14.6 | 28  |
| 4CE004BLVXZ | 4   | Cu | 0.7 | 1.8 | 2.5 | 15.8 | 36  |
| 4CE006BLVXZ | 6   | Cu | 0.7 | 1.8 | 2.5 | 17.0 | 45  |
| 4CE010BLVXZ | 10  | Cu | 0.7 | 1.8 | 4   | 19.4 | 65  |
| 4CE016BLVXZ | 16  | Cu | 0.7 | 1.8 | 6   | 21.9 | 92  |
| 4CE025BLVXZ | 25  | Cu | 0.9 | 1.8 | 6   | 24.7 | 130 |
| 4CE035BLVXZ | 35  | Cu | 0.9 | 1.8 | 10  | 27.5 | 175 |
| 4CE050BLVXZ | 50  | Cu | 1.0 | 2.0 | 16  | 31.4 | 236 |

The logo for NAN, consisting of the letters 'NAN' in a bold, red, sans-serif font.