

PVC Circular (0.6/1kV)



2, 3 & 4 core & earth, copper conductors, 0.6/1kV V-90 PVC insulated, 5V-90 PVC sheathed circular cable to AS/NZS 5000.1

Product Code	Nom. Cond. Area	Main Conductor Type	Nominal Insulation Thickness	Nominal Sheath Thickness	Earth Cond. Area	Nominal Overall Diameter	Approx. Mass
	mm ²		mm	mm	mm ²	mm	kg/100m

2 Core & Earth

2CE915C010C	1.5	Stranded Cu	0.8	1.8	1.5	10.8	14.4
2CE925C010C	2.5	Stranded Cu	0.8	1.8	2.5	11.9	19.0
2CE004C010C	4	Stranded Cu	1.0	1.8	2.5	13.2	24.2
2CE006C010C	6	Stranded Cu	1.0	1.8	2.5	14.0	29.1

3 Core & Earth

3CE915C010C	1.5	Stranded Cu	0.8	1.8	1.5	10.8	14.4
3CE925C010C	2.5	Stranded Cu	0.8	1.8	2.5	11.9	19.0
3CE004C010C	4	Stranded Cu	1.0	1.8	2.5	13.2	24.2
3CE006C010C	6	Stranded Cu	1.0	1.8	2.5	15.5	37.7

4 Core & Earth

4CE915C010C	1.5	Stranded Cu	0.8	1.8	1.5	12.5	20.1
4CE925C010C	2.5	Stranded Cu	0.8	1.8	2.5	13.8	27.3
4CE004C010C	4	Stranded Cu	1.0	1.8	2.5	15.8	37.1
4CE006C010C	6	Stranded Cu	1.0	1.8	2.5	17.1	46.5

Note:

Earth cores below 25mm² are not compacted.



NAN