

PVC Circular (450/750V)



2, 3 & 4 core & earth, copper conductors, 450/750kV V-90 PVC insulated, 5V-90 PVC sheathed circular cable to AS/NZS 5000.2

Product Code	Nom. Cond. Area	Main Conductor Type	Nominal Insulation Thickness	Nominal Sheath Thickness	Earth Cond. Area	Nominal Overall Diameter	Approx. Mass
	mm ²		mm	mm	mm ²	mm	kg/100m

2 Core & Earth

2CE915CLVOC	1.5	Stranded Cu	0.6	1.2	1.5	8.9	10.9
2CE925CLVOC	2.5	Stranded Cu	0.7	1.2	2.5	10.4	16.1
2CE004CLVOC	4	Stranded Cu	0.8	1.3	2.5	11.7	21.1
2CE006CLVOC	6	Stranded Cu	0.8	1.3	2.5	12.7	26.1

3 Core & Earth

3CE915CLVOC	1.5	Stranded Cu	0.6	1.2	1.5	9.6	14.4
3CE925CLVOC	2.5	Stranded Cu	0.7	1.2	2.5	11.5	19.0
3CE004CLVOC	4	Stranded Cu	0.8	1.3	2.5	12.9	24.2
3CE006CLVOC	6	Stranded Cu	0.8	1.3	2.5	13.8	37.7

4 Core & Earth

4CE915CLVOC	1.5	Stranded Cu	0.6	1.2	1.5	10.4	15.8
4CE925CLVOC	2.5	Stranded Cu	0.7	1.2	2.5	12.5	24.5
4CE004CLVOC	4	Stranded Cu	0.8	1.3	2.5	14.3	33.9
4CE006CLVOC	6	Stranded Cu	0.8	1.3	2.5	15.5	43.0

Note:

Earth cores below 25mm² are not compacted.



NAN