

# PVC TPS



2 core & earth, copper conductors, 450/750V V-90 PVC insulated,  
3V-90 PVC sheathed flat cable to AS/NZS 5000.2

Product Code	Nom. Cond. Area mm <sup>2</sup>	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Earth Cond. Area mm <sup>2</sup>	Nominal Overall Diameter mm	Approx. Mass kg/100m
--------------	------------------------------------	---------------------	------------------------------------	--------------------------------	-------------------------------------	--------------------------------	-------------------------

## 2 Core & Earth

2CE001SLVTP	1.0	Solid Cu	0.6	0.9	1.0	4.1 x 8.8	7.27
2CE915CLVTP	1.5	Stranded Cu	0.6	0.9	1.5	9.8 x 4.5	9.27
2CE925CLVTP	2.5	Stranded Cu	0.7	1.0	2.5	12.1 x 5.4	14.46
2CE004CLVTP	4	Stranded Cu	0.8	1.1	2.5	13.8 x 6.3	19.36
2CE006CLVTP	6	Stranded Cu	0.8	1.1	2.5	14.9 x 6.8	23.97
2CE010CLVTP	10	Stranded Cu	1.0	1.2	4.0	18.5 x 8.4	38.17
2CE016CLVTP	16	Stranded Cu	1.0	1.3	6.0	21.3 x 9.6	54.23

## 3 Core & Earth (Blue Sheath for Air Conditioning)

3CE915CLVTE	1.5	Stranded Cu	0.6	0.9	1.5	12.4 x 4.5	11.0
3CE925CLVTE	2.5	Stranded Cu	0.7	1.0	2.5	15.5 X 5.4	17.3



# NAN