

PVC TPS



2 core, copper conductors, 450/750V V-90 PVC insulated,
3V-90 PVC sheathed flat cable to AS/NZS 5000.2

| Product Code | Nom. Cond. Area mm ² | Main Conductor Type | Nominal Insulation Thickness mm | Nominal Sheath Thickness mm | Nominal Overall Diameter mm | Approx. Mass kg/100m |
|--------------|---------------------------------|---------------------|---------------------------------|-----------------------------|-----------------------------|----------------------|
|--------------|---------------------------------|---------------------|---------------------------------|-----------------------------|-----------------------------|----------------------|

2 Core Active (Red, White cores)

| | | | | | | |
|-------------|-----|-------------|-----|-----|------------|------|
| 2CA001SLVTP | 1.0 | Solid Cu | 0.6 | 0.9 | 6.4 x 4.1 | 5.3 |
| 2CA915CLVTP | 1.5 | Stranded Cu | 0.6 | 0.9 | 7.2 x 4.5 | 6.6 |
| 2CA925CLVTP | 2.5 | Stranded Cu | 0.7 | 1.0 | 8.7 x 5.4 | 10.2 |
| 2CA004CLVTP | 4 | Stranded Cu | 0.8 | 1.1 | 10.4 x 6.3 | 15.0 |
| 2CA006CLVTP | 6 | Stranded Cu | 0.8 | 1.1 | 11.5 x 6.8 | 19.5 |
| 2CA010CLVTP | 10 | Stranded Cu | 1.0 | 1.2 | 14.4 x 8.4 | 31.2 |
| 2CA016CLVTP | 16 | Stranded Cu | 1.0 | 1.3 | 16.6 x 9.6 | 44.8 |

2 Core (Red, Black Cores)

| | | | | | | |
|-------------|-----|-------------|-----|-----|------------|------|
| 2CS001SLVTP | 1.0 | Solid Cu | 0.6 | 0.9 | 6.4 x 4.1 | 5.3 |
| 2CS915CLVTP | 1.5 | Stranded Cu | 0.6 | 0.9 | 7.2 x 4.5 | 6.6 |
| 2CS925CLVTP | 2.5 | Stranded Cu | 0.7 | 1.0 | 8.7 x 5.4 | 10.2 |
| 2CS004CLVTP | 4 | Stranded Cu | 0.8 | 1.1 | 10.4 x 6.3 | 15.0 |
| 2CS006CLVTP | 6 | Stranded Cu | 0.8 | 1.1 | 11.5 x 6.8 | 19.5 |
| 2CS010CLVTP | 10 | Stranded Cu | 1.0 | 1.2 | 14.4 x 8.4 | 31.2 |
| 2CS016CLVTP | 16 | Stranded Cu | 1.0 | 1.3 | 16.6 x 9.6 | 44.8 |



NAN