

Flexible Cords - Heavy Duty PVC



Copper flexible conductors

0.6/1kV V-90 insulated and PVC sheathed

Heavy duty flexible cord to AS/NZS 3191

Product Code	Nominal Conductor Area mm ²	Maximum Diameter of Wires mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
--------------	--	------------------------------	-----------------------------	----------------------

2 Core

2CF975FHDPV	0.75	0.21	8.1	8
2CF001FHDPV	1.0	0.21	8.4	10
2CF915FHDPV	1.5	0.26	9.3	12
2CF925FHDPV	2.5	0.26	11.1	18
2CF004FHDPV	4	0.31	12.8	25

3 Core (2 Core & Earth)

3CF975FHDPV	0.75	0.21	8.7	10
3CF001FHDPV	1.0	0.21	9.1	12
3CF915FHDPV	1.5	0.26	10.1	15
3CF925FHDPV	2.5	0.26	11.9	22
3CF004FHDPV	4	0.31	13.7	30

4 Core (3 Core & Earth)

4CF975FHDPV	0.75	0.21	9.6	12
4CF001FHDPV	1.0	0.21	10.0	14
4CF915FHDPV	1.5	0.26	11.1	18
4CF925FHDPV	2.5	0.26	13.1	26
4CF004FHDPV	4	0.31	15.1	37

Note:

Flexible cord core colours are:

2 Core: Brown, Light Blue

3 Core: Brown, Light Blue, Green/Yellow

4 Core: Brown, Light Blue, White, Green/Yellow

Sheath colour: orange

Light blue is normally used as a neutral (where applicable)



NAN