

Flexible Cords - Ordinary Duty PVC



Copper flexible conductors
250/440V V-90 insulated and sheathed
Ordinary duty flexible cord to AS/NZS 3191

Product Code	Nominal Conductor Area mm ²	Maximum Diameter of Wires mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
--------------	----------------------------------------	------------------------------	-----------------------------	----------------------

2 Core

2CF975FODPV	0.75	0.21	6.3	6
2CF001FODPV	1.0	0.21	6.6	6
2CF915FODPV	1.5	0.26	7.5	9
2CF925FODPV	2.5	0.26	9.3	14
2CF004FODPV	4	0.31	10.4	18

3 Core (2 Core & Earth)

3CF975FODPV	0.75	0.21	6.6	7
3CF001FODPV	1.0	0.21	7.0	8
3CF915FODPV	1.5	0.26	8.2	11
3CF925FODPV	2.5	0.26	10.1	17
3CF004FODPV	4	0.31	11.2	23

4 Core (3 Core & Earth)

4CF975FODPV	0.75	0.21	7.2	8
4CF001FODPV	1.0	0.21	7.9	10
4CF915FODPV	1.5	0.26	9.2	14
4CF925FODPV	2.5	0.26	11.0	21
4CF004FODPV	4	0.31	12.3	29

Note:

Flexible cord core colours are:

2 Core: Brown, Light Blue

3 Core: Brown, Light Blue, Green/Yellow

4 Core: Brown, Light Blue, White, Green/Yellow

Sheath colour: grey

Light blue is normally used as a neutral (where applicable)



NAN