

Variable Speed Drive Cables

3 core & 3 earth*, copper conductors, 0.6/1kV X-90 insulated, PVC bedded, copper-tape screened, black 5V-90 PVC Sheathed to AS/NZS 5000.1

Product Code	Nom. Cond. Area mm ²	Main Cond. Type	Nom. Ins Thick. mm	Earth Cond. Area mm ²	Nom. Diam. Over screen mm	Nom. Sheath Thick. mm ²	Nom. Overall Dia. mm	Approx. Mass kg/100m
VSD915CLVXB	1.5	Cu	0.7	1 x 1.5	9.1	1.8	12.7	22
VSD925CLVXB	2.5	Cu	0.7	1 x 2.5	10.2	1.8	13.8	28
VSD004CLVXB	4	Cu	0.7	3 x 1.5	11.3	1.8	14.9	36
VSD006CLVXB	6	Cu	0.7	3 x 1.5	12.5	1.8	16.2	44
VSD010CLVXB	10	Cu	0.7	3 x 1.5	14.5	1.8	18.1	59
VSD016CLVXB	16	Cu	0.7	3 x 2.5	16.7	1.8	20.3	83
VSD025CLVXB	25	Cu	0.9	3 x 4	19.5	1.8	23.1	117
VSD035CLVXB	35	Cu	0.9	3 x 6	21.7	1.8	25.3	154
VSD050CLVXB	50	Cu	1.0	3 x 10	24.7	1.9	28.4	207
VSD070CLVXB	70	Cu	1.1	3 x 10	29.4	2.0	33.5	279
VSD095CLVXB	95	Cu	1.1	3 x 16	32.8	2.1	37.1	375
VSD120CLVXB	120	Cu	1.2	3 x 16	36.5	2.3	41.1	455
VSD150CLVXB	150	Cu	1.4	3 x 25	41.0	2.4	45.9	581
VSD185CLVXB	185	Cu	1.6	3 x 25	51.0	2.6	51.0	701

NAN