


XLPE/PVC Copper SDI



Single core, copper conductors, 0.6/1kV X-90 XLPE insulated,
5V-90 PVC sheathed to AS/NZS 5000.1

| Product Code | Nominal Conductor Area mm ² | Main Conductor Type | Nominal Insulation Thickness mm | Nominal Sheath Thickness mm | Nominal Overall Diameter mm | Approx. Mass kg/100m |
|--------------|--|---------------------|---------------------------------|-----------------------------|-----------------------------|----------------------|
| XSD016CLCNB | 16 | Stranded Cu | 0.8 | 1.4 | 9.4 | 21.5 |
| XSD025CLVNB | 25 | Compact Cu | 0.9 | 1.4 | 10.5 | 30.7 |
| XSD035CLVNB | 35 | Compact Cu | 0.9 | 1.4 | 11.5 | 40.1 |
| XSD050CLVNB | 50 | Compact Cu | 1.0 | 1.4 | 12.9 | 52.7 |
| XSD070CLVNB | 70 | Compact Cu | 1.1 | 1.4 | 14.9 | 73.5 |
| XSD095CLVNB | 95 | Compact Cu | 1.1 | 1.5 | 16.7 | 99.3 |
| XSD120CLVNB | 120 | Compact Cu | 1.2 | 1.5 | 18.4 | 123 |
| XSD150CLVNB | 150 | Compact Cu | 1.4 | 1.6 | 20.5 | 152 |
| XSD185CLVNB | 185 | Compact Cu | 1.6 | 1.6 | 22.7 | 188 |
| XSD240CLVNB | 240 | Compact Cu | 1.7 | 1.7 | 25.3 | 244 |
| XSD300CLVNB | 300 | Compact Cu | 1.8 | 1.8 | 27.8 | 303 |
| XSD400CLVNB | 400 | Compact Cu | 2.0 | 1.9 | 31.3 | 386 |
| XSD500CLVNB | 500 | Compact Cu | 2.2 | 2.0 | 35.0 | 491 |
| XSD630CLVNB | 630 | Compact Cu | 2.4 | 2.2 | 39.2 | 632 |



NAN