


# PVC TPS

2 core, copper conductors, 450/750V V-90 PVC insulated,  
3V-90 PVC sheathed flat cable to AS/NZS 5000.2



Product Code	Nom. Cond. Area mm <sup>2</sup>	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
--------------	---------------------------------	---------------------	---------------------------------	-----------------------------	-----------------------------	----------------------

### 2 Core Active (Red, White cores)

2CA001SLVTP	1.0	Solid Cu	0.6	0.9	6.4 x 4.1	4.1
2CA915CLVTP	1.5	Stranded Cu	0.6	0.9	7.2 x 4.5	6.4
2CA925CLVTP	2.5	Stranded Cu	0.7	1.0	8.7 x 5.4	9.6
2CA004CLVTP	4	Stranded Cu	0.8	1.1	10.4 x 6.3	15
2CA006CLVTP	6	Stranded Cu	0.8	1.1	11.5 x 6.8	19
2CA010CLVTP	10	Stranded Cu	1.0	1.2	14.4 x 8.4	30
2CA016CLVTP	16	Stranded Cu	1.0	1.3	16.6 x 9.6	43

### 2 Core (Red, Black Cores)

2CS001SLVTP	1.0	Solid Cu	0.6	0.9	6.4 x 4.1	4.1
2CS915CLVTP	1.5	Stranded Cu	0.6	0.9	7.2 x 4.5	6.4
2CS925CLVTP	2.5	Stranded Cu	0.7	1.0	8.7 x 5.4	9.6
2CS004CLVTP	4	Stranded Cu	0.8	1.1	10.4 x 6.3	15
2CS006CLVTP	6	Stranded Cu	0.8	1.1	11.5 x 6.8	19
2CS010CLVTP	10	Stranded Cu	1.0	1.2	14.4 x 8.4	30
2CS016CLVTP	16	Stranded Cu	1.0	1.3	16.6 x 9.6	43

