

Three Core Al 19/33kV XLPE Insulated HD Cu Screened PVC Sheathed

STANDARD: AS/NZS 1429.1

RATED VOLTAGE: 19/33 (36) kV

FAULT LEVEL: Up to 10kA for 1 sec or to customer requirements

IMPULSE VOLTAGE: 95kV

TEMPERATURE RANGE:

In continuous operations Max. conductor temp 90°C

Lowest cable temperature during installation: -10°C and below 0°C special precautions must be taken.

BENDING RADIUS:

During installation: 18 x D. When installed: 12 x D (PVC sheathed cables)

D = Overall diameter of cable

DESIGN

CONDUCTOR:

Stranded, round and compacted aluminium complying with AS/NZS 1125

SEMI-CONDUCTIVE CONDUCTOR SCREEN:

Extruded cross-linked compound

INSULATION:

XLPE complying with AS/NZS 3808

SEMI-CONDUCTIVE INSULATION SCREEN:

Extruded hand strippable semi-conductive cross-linked compound

METALLIC SCREEN:

Circular copper wires

OUTER SHEATH:

Black PVC as standard. HDPE, halogen free, flame retardant, termite protection in the form of nylon, double brass tape or chemical additive also available.





Product Code	Conductor size mm ²	Nominal insulation thickness mm	Diameter over insulation mm	Number & diameter of screen wires no./mm	Overall Diameter mm	Mass (approx.) kg/km	Maximum pulling tension kN	Minimum Bending Radius	
								During installation mm	Installed mm
3MV050A33HP	50	8.0	25.3	19/0.85	68.6	3600	7.5	1230	820
3MV070A33HP	70	8.0	27.1	27 /0.85	72.7	4200	11	1310	870
3MV095A33HP	95	8.0	28.7	36/0.85	76.4	4800	14	1380	920
3MV120A33HP	120	8.0	30.2	40/0.85	79.9	5400	18	1440	960
3MV150A33HP	150	8.0	31.7	40/0.85	83.3	5900	23	1500	1000
3MV185A33HP	185	8.0	33.5	40/0.85	87.5	6500	25	1570	1050
3MV240A33HP	240	8.0	35.7	40/0.85	92.5	7400	25	1670	1110
3MV300A33HP	300	8.0	37.8	40/0.85	97.4	8300	25	1750	1170
3MV400A33HP	400	8.0	40.7	40/0.85	104.1	9600	25	1870	1250
3MV500A33HP	500	8.0	46.8	40/0.85	118.1	12000	25	2130	1420

Three Core Al 19/33kV XLPE Insulated HD Cu Screened PVC Sheathed

Electrical Data

Product Code	Conductor size mm ²	Max. conductor DC resistance at 20°C Ω/km	Conductor AC resistance at 50Hz and 90°C Ω/km	Inductive reactance at 50Hz and 90°C Ω/km	Insulation resistance at 20°C MΩ.km	Charging current per phase A/km	Dielectric loss per phase W/km	Zero sequence resistance at 20°C Ω/km	Zero sequence reactance at 50Hz Ω/km
3MV050A33HP	50	0.641	0.822	0.143	17000	0.828	15.7	2.32	0.0976
3MV070A33HP	70	0.443	0.568	0.131	16000	0.929	17.6	1.62	0.0862
3MV095A33HP	95	0.320	0.411	0.125	14000	1.02	19.3	1.20	0.0801
3MV120A33HP	120	0.253	0.325	0.120	13000	1.10	20.9	1.05	0.0753
3MV150A33HP	150	0.206	0.265	0.116	12000	1.18	22.4	1.00	0.0713
3MV185A33HP	185	0.164	0.211	0.112	11000	1.28	24.3	0.961	0.0671
3MV240A33HP	240	0.125	0.161	0.108	10000	1.39	26.5	0.922	0.0629
3MV300A33HP	300	0.100	0.130	0.104	9600	1.51	28.6	0.897	0.0595
3MV400A33HP	400	0.0778	0.102	0.0995	8700	1.66	31.5	0.875	0.0548
3MV500A33HP	500	0.0617	0.0815	0.0969	7700	1.86	35.4	0.859	0.0523

Current Ratings

Conductor Size mm ²	Current rating at core temp. 90°C in ground A 	Current rating at core temp. 90°C in air A 	Max. short-circuit current on the conductor during 1sec at initial temp. 90°C kA	Short circuit current rating of the screen 1 sec. kA
50	158	158	4.7	4.8
70	194	197	6.6	6.8
95	231	238	9.0	9.1
120	263	273	11.3	10.1
150	295	309	14.2	10.1
185	334	354	17.5	10.1
240	387	416	22.7	10.1
300	437	475	28.4	10.1
400	501	552	37.8	10.1
500	557	616	47.3	10.1