

4 Core & Earth Fire Rated

4 core & earth, copper conductors, 0.6/1kV X-HF-110 insulated, Orange HFS-110-TP Sheathed to AS/NZS 5000.1
WS52W rated to AS/NZS 3013



Product Code	Nominal Conductor Area mm ²	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Earth Conductor Area mm ²	Nominal Overall Diameter mm	Approx. Mass kg/100m
--------------	---	---------------------	------------------------------------	--------------------------------	---	--------------------------------	-------------------------

4 Core & Earth

4CE915DLVXZ	1.5	Cu	0.8	1.8	1.5	16.1	37
4CE925DLVXZ	2.5	Cu	0.8	1.8	2.5	17.5	45
4CE004DLVXZ	4	Cu	1.0	1.8	2.5	18.6	55
4CE006DLVXZ	6	Cu	1.0	1.8	2.5	19.9	65
4CE010DLVXZ	10	Cu	1.0	1.8	4	22.3	90
4CE016DLVXZ	16	Cu	1.0	1.8	6	24.8	120
4CE025DLVXZ	25	Cu	1.2	1.8	6	28.0	170
4CE035DLVXZ	35	Cu	1.2	1.8	10	30.7	225
4CE050DLVXZ	50	Cu	1.4	1.8	16	34.5	295
4CE070DLVXZ	70	Cu	1.4	1.9	25	39.8	410
4CE095DLVXZ	95	Cu	1.6	2.0	25	44.8	530
4CE120DLVXZ	120	Cu	1.6	2.1	35	48.1	650