

110°C Halogen Free SDI

Single core, copper conductor, 0.6/1kV X-HF-110 XLPE insulated, HFS-110-TP sheathed to AS/NZS 5000.1



Product Code	Nominal Conductor Area mm ²	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
HSD035CLVNB	35	Cu	0.9	1.4	11.6	42
HSD050CLVNB	50	Cu	1.0	1.4	13.0	58
HSD070CLVNB	70	Cu	1.1	1.4	15.0	76
HSD095CLVNB	95	Cu	1.1	1.5	17.2	102
HSD120CLVNB	120	Cu	1.2	1.5	19.5	132
HSD150CLVNB	150	Cu	1.4	1.6	21.6	162
HSD185CLVNB	185	Cu	1.6	1.6	23.9	200
HSD240CLVNB	240	Cu	1.7	1.7	26.3	251
HSD300CLVNB	300	Cu	1.8	1.8	28.0	320
HSD400CLVNB	400	Cu	2.0	1.9	31.6	400
HSD500CLVNB	500	Cu	2.2	2.0	35.2	510
HSD630CLVNB	630	Cu	2.4	2.2	39.2	660

