

PVC Circular (0.6/1kV)

2, 3 & 4 core & earth, copper conductors, 0.6/1kV V-90 PVC insulated, 5V-90 PVC sheathed circular cable to AS/NZS 5000.1



Product Code	Nom. Cond. Area mm ²	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Earth Conductor Area mm ²	Nominal Overall Diameter mm	Approx. Mass kg/100m
2 Core & Earth							
2CE915C010C	1.5	Stranded Cu	0.8	1.8	1.5	10.6	16
2CE925C010C	2.5	Stranded Cu	0.8	1.8	2.5	11.9	21
2CE004C010C	4	Stranded Cu	1.0	1.8	2.5	13.4	27
2CE006C010C	6	Stranded Cu	1.0	1.8	2.5	14.0	33
3 Core & Earth							
3CE915C010C	1.5	Stranded Cu	0.8	1.8	1.5	10.8	17
3CE925C010C	2.5	Stranded Cu	0.8	1.8	2.5	12.9	24
3CE004C010C	4	Stranded Cu	1.0	1.8	2.5	14.6	30
3CE006C010C	6	Stranded Cu	1.0	1.8	2.5	15.6	38
4 Core & Earth							
4CE915C010C	1.5	Stranded Cu	0.8	1.8	1.5	12.4	21
4CE925C010C	2.5	Stranded Cu	0.8	1.8	2.5	13.9	30
4CE004C010C	4	Stranded Cu	1.0	1.8	2.5	15.9	40
4CE006C010C	6	Stranded Cu	1.0	1.8	2.5	17.2	51



Note:
Earth cores below 25mm² are not compacted.