

Multicore & earth, copper conductors, 0.6/1kV V-90 PVC insulated (numbered), Black PVC sheathed to AS/NZS 5000.1



Product Code	Number of Cores	Nominal Overall Diameter mm	Approx. Mass kg/100m
<b>1.5mm<sup>2</sup> (7/0.50mm)</b>			
6CE915CLVCC	6+E	13.4	24.5
8CE915CLVCC	8+E	15.8	30.9
10E915CLVCC	10+E	16.4	36.2
12E915CLVCC	12+E	17.7	41.3
15E915CLVCC	15+E	18.7	48.7
16E915CLVCC	16+E	19.5	51.9
20E915CLVCC	20+E	20.5	61.1
25E915CLVCC	25+E	22.7	73.3
30E915CLVCC	30+E	24.7	85.8
36E915CLVCC	36+E	25.7	99.6
40E915CLVCC	40+E	27.7	113
50E915CLVCC	50+E	30.2	135
<b>2.5mm<sup>2</sup> (7/0.67mm)</b>			
6CE925CLVCC	6+E	15.1	34.4
8CE925CLVCC	8+E	17.7	44.1
10E925CLVCC	10+E	18.5	51.9
12E925CLVCC	12+E	19.9	59.8
15E925CLVCC	15+E	21.0	69.5
16E925CLVCC	16+E	22.0	74.1
20E925CLVCC	20+E	23.2	89.1
25E925CLVCC	25+E	25.6	106
30E925CLVCC	30+E	28.1	126
36E925CLVCC	36+E	29.2	146
40E925CLVCC	40+E	31.7	163
50E925CLVCC	50+E	34.6	200

