


Flexible Cords - Heavy Duty PVC

Copper flexible conductors, 0.6/1kV V-90 PVC insulated and sheathed. Heavy duty flexible cord to AS/NZS 3191



Product Code	Nominal Conductor Area mm ²	Maximum Diameter of Wires mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
2 Core				
2CF975FHDOG	0.75	0.21	8.1	8.5
2CF001FHDOG	1.0	0.21	8.3	9.5
2CF915FHDOG	1.5	0.26	9.2	12.0
2CF925FHDOG	2.5	0.26	11.0	17.5
2CF004FHDOG	4	0.31	12.8	25.0
3 Core (2 Core & Earth)				
3CF975FHDOG	0.75	0.21	8.7	10.2
3CF001FHDOG	1.0	0.21	9.0	11.5
3CF915FHDOG	1.5	0.26	10.0	14.6
3CF925FHDOG	2.5	0.26	11.8	21.4
3CF004FHDOG	4	0.31	14.9	36.0
4 Core (3 Core & Earth)				
4CF975FHDOG	0.75	0.21	9.6	12.0
4CF001FHDOG	1.0	0.21	10.0	14.0
4CF915FHDOG	1.5	0.26	11.1	18.0
4CF925FHDOG	2.5	0.26	12.9	26.2
4CF004FHDOG	4	0.31	14.9	37.0

Note:

Flexible cord core colours are:

2 Core: Brown, Light Blue

3 Core: Brown, Light Blue, Green/Yellow

4 Core: Brown, Light Blue, White, Green/Yellow

Light blue is normally used as a neutral (where applicable)

