


Flexible Cords - Ordinary Duty PVC

Copper flexible conductors, 250/440V V-90 PVC insulated and sheathed. Ordinary duty flexible cord to AS/NZS 3191



Product Code	Nominal Conductor Area mm ²	Maximum Diameter of Wires mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
--------------	-------------------------------------------	---------------------------------	--------------------------------	-------------------------

2 Core

2CF975FODGR	0.75	0.21	6.3	8.5
2CF001FODGR	1.0	0.21	6.6	9.5
2CF915FODGR	1.5	0.26	7.5	12.0
2CF925FODGR	2.5	0.26	9.3	17.5

3 Core (2 Core & Earth)

3CF975FODGR	0.75	0.21	6.6	6.7
3CF001FODGR	1.0	0.21	6.9	7.8
3CF915FODGR	1.5	0.26	8.1	10.9
3CF925FODGR	2.5	0.26	9.9	17.0
3CF004FODGR	4	0.31	11.1	22.5

4 Core (3 Core & Earth)

4CF975FODGR	0.75	0.21	7.2	8.0
4CF001FODGR	1.0	0.21	7.8	10.0
4CF915FODGR	1.5	0.26	9.2	14.0
4CF925FODGR	2.5	0.26	10.9	20.8
4CF004FODGR	4	0.31	12.1	27.8

Note:

Flexible cord core colours are:

2 Core: Brown, Light Blue

3 Core: Brown, Light Blue, Green/Yellow

4 Core: Brown, Light Blue, White, Green/Yellow

