

# PVC SWA Circular

2, 3 & 4 core & earth, copper conductors, 0.6/1kV V-90 PVC insulated, PVC bedded, steel wire armoured, 5V-90 PVC sheathed circular cable to AS/NZS 5000.1



Product Code	Nom. Cond. Area mm <sup>2</sup>	Main Conductor Type	Nominal Insulation Thickness mm	Earth Cond. Area mm <sup>2</sup>	Nom. Dia. Over Bedding mm	Nom. Dia. Over Armour mm	Nom. Overall Dia. mm	Approx. Mass kg/100m
--------------	------------------------------------	---------------------	------------------------------------	-------------------------------------	------------------------------	-----------------------------	-------------------------	-------------------------

## 2 Core & Earth

2CE915CLVOS	1.5	Stranded Cu	0.8	1.5	9.1	10.7	14.9	37.2
2CE925CLVOS	2.5	Stranded Cu	0.8	2.5	10.3	11.9	16.1	44.5
2CE004CLVOS	4	Stranded Cu	1.0	2.5	11.8	13.4	17.6	53.5
2CE006CLVOS	6	Stranded Cu	1.0	2.5	12.9	14.5	18.7	61.2

## 3 Core & Earth

3CE915CLVOS	1.5	Stranded Cu	0.8	1.5	9.9	11.5	15.7	41.9
3CE925CLVOS	2.5	Stranded Cu	0.8	2.5	11.3	12.9	17.1	50.8
3CE004CLVOS	4	Stranded Cu	1.0	2.5	13.0	15.5	19.7	76.3
3CE006CLVOS	6	Stranded Cu	1.0	2.5	14.0	16.5	20.7	86

## 4 Core & Earth

4CE915CLVOS	1.5	Stranded Cu	0.8	1.5	10.9	12.5	15.6	40.6
4CE925CLVOS	2.5	Stranded Cu	0.8	2.5	12.3	13.9	17.0	66.8
4CE004CLVOS	4	Stranded Cu	1.0	2.5	14.4	16.9	20.0	80.5
4CE006CLVOS	6	Stranded Cu	1.0	2.5	15.6	18.1	22.8	95.1



Note:  
Earth cores below 25mm<sup>2</sup> are not compacted.