

Single Core Flexible Fire Rated

Class 5 flexible copper conductors, mica taped,
0.6/1kV X-HF-110 insulated, HFS-110-TP sheathed (black) to
AS/NZS 5000.1 and WS52W rated to AS/NZS 3013



Product Code	Nominal Conductor Area mm ²	Main Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
HSD035BLVNB	35	Flex Cu	0.9	1.4	14.7	48
HSD050BLVNB	50	Flex Cu	1.0	1.5	16.8	65
HSD070BLVNB	70	Flex Cu	1.1	1.5	18.8	87
HSD095BLVNB	95	Flex Cu	1.1	1.6	20.6	110
HSD120BLVNB	120	Flex Cu	1.2	1.7	22.3	140
HSD150BLVNB	150	Flex Cu	1.4	1.8	25.0	170
HSD185BLVNB	185	Flex Cu	1.6	1.9	27.1	205
HSD240BLVNB	240	Flex Cu	1.7	2.0	30.1	265
HSD300BLVNB	300	Flex Cu	1.8	2.1	33.2	325
HSD400BLVNB	400	Flex Cu	2.0	2.2	39.3	410