

Variable Speed Drive Cables

3 core & 3 earth, copper conductors, 0.6/1kV X-90 XLPE insulated, PVC bedded, copper tape screened, black 5V-90 PVC sheathed to AS/NZS 5000.1

Product Code	Nom. Cond. Area mm ²	Main Cond. Type	Nom. Insulation Thick. mm	Earth Cond. Area mm ²	Nom. Diam. over Screen mm	Nom. Sheath Thick. mm ²	Nom. Overall Dia. mm	Approx. Mass kg/100m
VSD915CLVXB	1.5	Cu	0.7	1 x 1.5	9.1	1.8	12.7	22
VSD925CLVXB	2.5	Cu	0.7	1 x 2.5	10.2	1.8	14.4	33.1
VSD004CLVXB	4	Cu	0.7	3 x 1.5	11.3	1.8	14.9	36
VSD006CLVXB	6	Cu	0.7	3 x 1.5	12.5	1.8	16.1	46.2
VSD010CLVXB	10	Cu	0.7	3 x 1.5	14.5	1.8	18.1	65.1
VSD016CLVXB	16	Cu	0.7	3 x 2.5	16.7	1.8	20.3	88.5
VSD025CLVXB	25	Cu	0.9	3 x 4	19.5	1.8	23.1	126
VSD035CLVXB	35	Cu	0.9	3 x 6	21.7	1.8	25.3	145
VSD050CLVXB	50	Cu	1.0	3 x 10	24.7	1.9	31.1	219
VSD070CLVXB	70	Cu	1.1	3 x 10	29.4	2.0	33.5	279