


XLPE/PVC SDI

Single core, aluminium conductor, 0.6/1kV X-90 XLPE insulated, 5V-90 PVC sheathed to AS/NZS 5000.1



Product Code	Nominal Conductor Area mm ²	Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
XSD025ALVNB	25	Compact Al	0.9	1.4	10.7	15
XSD035ALVNB	35	Compact Al	0.9	1.4	11.5	19
XSD050ALVNB	50	Compact Al	1.0	1.4	12.9	23
XSD070ALVNB	70	Compact Al	1.1	1.4	14.9	34
XSD095ALVNB	95	Compact Al	1.1	1.5	16.7	40
XSD120ALVNB	120	Compact Al	1.2	1.5	18.4	49
XSD150ALVNB	150	Compact Al	1.4	1.6	20.5	61
XSD185ALVNB	185	Compact Al	1.6	1.6	22.7	75
XSD240ALVNB	240	Compact Al	1.7	1.7	25.3	95
XSD300ALVNB	300	Compact Al	1.8	1.8	27.8	115
XSD400ALVNB	400	Compact Al	2.0	1.9	31.3	150
XSD500ALVNB	500	Compact Al	2.2	2.0	35.0	185
XSD630ALVNB	630	Compact Al	2.4	2.2	39.2	235

