


# XLPE/PVC SDI

Single core, copper conductor, 0.6/1kV X-90 XLPE insulated, 5V-90 PVC sheathed to AS/NZS 5000.1



Product Code	Nominal Conductor Area mm <sup>2</sup>	Conductor Type	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm	Nominal Overall Diameter mm	Approx. Mass kg/100m
XSD016CLCNB	16	Stranded Cu	0.8	1.4	9.4	21
XSD025CLVNB	25	Compact Cu	0.9	1.4	10.6	30
XSD035CLVNB	35	Compact Cu	0.9	1.4	11.6	40
XSD050CLVNB	50	Compact Cu	1.0	1.4	13.0	52
XSD070CLVNB	70	Compact Cu	1.1	1.4	14.9	73
XSD095CLVNB	95	Compact Cu	1.1	1.5	16.7	98
XSD120CLVNB	120	Compact Cu	1.2	1.5	18.4	125
XSD150CLVNB	150	Compact Cu	1.4	1.6	20.5	155
XSD185CLVNB	185	Compact Cu	1.6	1.6	22.7	190
XSD240CLVNB	240	Compact Cu	1.7	1.7	25.3	245
XSD300CLVNB	300	Compact Cu	1.8	1.8	27.8	300
XSD400CLVNB	400	Compact Cu	2.0	1.9	31.3	385
XSD500CLVNB	500	Compact Cu	2.2	2.0	35.0	490
XSD630CLVNB	630	Compact Cu	2.4	2.2	39.2	625

